


 <p>Monitors Prosumer</p>	<p>KA220HQDbid Extra comfort</p>   
<p>Sub Model Product line</p>	<p>KA220HQD KA0 Series</p>
<p>General</p>	
<p>Display Type Dimensions (WxHxD mm) Min. Profile Thickness mm Net Weight (kg) Gross Weight (kg) Chassis colour and finish</p>	<p>Flat screen/TFT 509x390x207 18.5 3.5 4.9 Black Matt</p>
<p>Display</p>	
<p>Panel Technology Crystalbrite Size cm Size Inch Format Display dimensions (mm) Pixel Pitch (mm) Resolution Frequency (H/V) PPI Rsp time (ms) Dynamic Contrast ratio Brightness (cd/m2) H/V° CR 10:1 H/V° CR 5:1 Colors Bit Color Gamut Backlight type Screen coating hardness OS Compliance</p>	<p>IPS No 55 21.5 16:9 476.6x268.1 0.248 1920x1080@60HzHz 30-80Khz/55-75Hz 102 4 100M:1 250 178/178 178/178 16.7M 6Bit+Hi-FRC 72% NTSC LED 3H Win10 compliant</p>
<p>Video Input</p>	
<p>Input Signal</p>	<p>VGA + DVI (w/HDCP) + HDMI</p>
<p>Audio Input</p>	
<p>Speaker</p>	<p>No</p>
<p>Ergonomics</p>	
<p>VESA Wall Mounting Kensington Support Tilt Swivel degrees Hgt Adj (mm) Pivot degrees</p>	<p>100x100 Yes -5°~15° No No No</p>
<p>Power Supply</p>	
<p>Power Supply Energy Star Type Off/Standby (W) Sleep (W) Min On (W) Max (W) EEL Class Power On (W) Annual Energy Consumption (kWh/year) Mercury (mg) Lead</p>	<p>Internal ES7.0 0.25 0.35 19.5 - B 26 38 0 Presence*</p>
<p>Manufacturer Guarantee</p>	
<p>Warranty Certificates Certification MTBF Hours @ 25°C</p>	<p>EMEA Commercial (3yr) CE, TÜV GS, ISO9241-307 class II MPRII 30000</p>
<p>Pallet and Container Loading</p>	
<p>Pallet qty (pcs) Pallet Size (WxHxD) cm Container loading 20"/40" Package Dimensions (cm) Included cables</p>	<p>100 115x115x222 1000/2000 56.5x41.8x11.5 VGA</p>
<p>Special Features</p>	
<p>Wide Viewing Angle Flicker-Less Blue Light Filter Low Dimming Comfyview ZeroFrame</p>	<p>Wide Viewing Angle Flicker-Less Blue Light Filter Low Dimming Comfyview ZeroFrame</p>